

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2003-140361

(43)Date of publication of application : 14.05.2003

(51)Int.Cl.

G03F 7/40
G03F 7/039
H01L 21/027

(21)Application number : 2001-334170

(71)Applicant : MATSUSHITA ELECTRIC IND CO
LTD

(22)Date of filing : 31.10.2001


(72)Inventor : ENDO MASATAKA
SASAKO MASARU

(54) METHOD FOR FORMING PATTERN

(57)Abstract:

PROBLEM TO BE SOLVED: To reduce dispersion in the size of a resist pattern.

SOLUTION: After a resist film 11 consisting of a chemically amplifying resist material containing a base polymer containing at least one ester of acrylate and methacrylate and an acid generating agent which generates acid by irradiation of light is formed, the resist film 11 is selectively irradiated with extreme UV rays 13 for pattern exposure. The resist film 11 subjected to the pattern exposure is developed to form a resist pattern 15 consisting of the non-exposed part of the resist film 11. The resist pattern 15 is heated to smoothen the roughness 15a of the pattern 15.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

